



3-IN-ONE.



Safety Data Sheet



1 - Identification

Product Name: 3-IN-ONE® Multi-Purpose PTFE LUBRICANT	Manufacturer: WD-40 Company Address: 1061 Cudahy Place (92110) P.O. Box 80607 San Diego, California, USA 92138 -0607
Product Use: Lubricant and Protectant	Telephone: Emergency only: 1-888-324-7596 (PROSAR) Information: 1-888-324-7596 Chemical Spills: 1-800-424-9300 (Chemtrec) 1-703-527-3887 (International Calls)
Restrictions on Use: None identified	
SDS Date Of Preparation: March 7, 2016	

2 – Hazards Identification

Hazcom 2012/GHS Classification:

- Flammable Liquid Category 2
- Aspiration Toxicity Category 1
- Skin Irritation Category 2
- Specific Organ Toxicity Single Exposure Category 3 (Nervous System)

Note: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Label Elements:



DANGER!

- Highly flammable liquid and vapor.
- May be fatal if swallowed and enters airways.
- Causes skin irritation.
- May cause drowsiness or dizziness.

Prevention

- Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
- Keep container tightly closed.
- Ground and bond container and receiving equipment
- Use explosion-proof electrical, ventilating and lighting equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid breathing mist, vapors or spray.
- Wash thoroughly after handling.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves and eye protection.

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with soap and water.

If skin irritation occurs: Get medical attention. Wash contaminated clothing before reuse.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER or doctor if you feel unwell.
 IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
 In case of fire: Use water fog, dry chemical, carbon dioxide or foam to extinguish.

Storage

Store in a well-ventilated place. Keep cool. Keep container tightly closed.
 Store locked up.

Disposal

Dispose of contents and container in accordance with local and national regulations

3 - Composition/Information on Ingredients

Ingredient	CAS #	Weight Percent	US Hazcom 2012/ GHS Classification
Aliphatic Hydrocarbon (LVP)	64742-47-8	45-50	Flammable Liquid Category 3 Aspiration Toxicity Category 1
Heptane	64742-49-0 142-82-5	20-40	Aspiration Toxicity Category 1 Flammable Liquid Category 2 Skin Irritant Category 2 Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)
Petroleum Oils	64742-56-9 64742-65-0 64742-53-6 64742-54-7 64742-71-8	<20	Not Hazardous
Non-Hazardous Ingredients	Mixture	<10	Not Hazardous

Note: The exact percentages are a trade secret.

4 – First Aid Measures

Ingestion (Swallowed): Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.

Eye Contact: Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes. Get medical attention if irritation persists.

Skin Contact: Wash with soap and water. If irritation develops and persists, get medical attention.

Inhalation (Breathing): If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

Signs and Symptoms of Exposure: Harmful or fatal if swallowed. If swallowed, may be aspirated and cause lung damage. May cause eye, skin and respiratory irritation. Inhalation of vapors may cause irritation, dizziness and drowsiness.. Skin contact may cause drying of the skin.

Indication of Immediate Medical Attention/Special Treatment Needed: Immediate medical attention is needed for ingestion.

5 – Fire Fighting Measures

Suitable (and unsuitable) Extinguishing Media: Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and spread fire. Cool fire exposed containers with water.

Specific Hazards Arising from the Chemical: Extremely Flammable liquid and vapor. Vapors can cause a flash fire. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. A vapor and air mixture can create an explosion hazard in confined spaces.

Special Protective Equipment and Precautions for Fire-Fighters: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water.

6 – Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Wear appropriate protective clothing (see Section 8). Eliminate all sources of ignition and ventilate area.

Methods and Materials for Containment/Cleanup: Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required.

7 – Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors or aerosols. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children.

Conditions for Safe Storage: Store in a cool, well-ventilated area, away from incompatible materials. NFPA Class IB Liquid.

8 – Exposure Controls/Personal Protection

Chemical	Occupational Exposure Limits
Aliphatic Hydrocarbon	1200 mg/m ³ TWA (manufacturer recommended)
Heptane	500 ppm TWA OSHA PEL 500 ppm Skin TWA, 400 ppm STEL ACGIH TLV
Petroleum Oils	5 mg/m ³ (inhalable) TWA ACGIH TLV 5 mg/m ³ TWA OSHA PEL
Non-Hazardous Ingredients	None Established

The Following Controls are Recommended for Normal Consumer Use of this Product

Appropriate Engineering Controls: Use in a well-ventilated area.

Personal Protection:

Eye Protection: Avoid eye contact.

Skin Protection: Avoid prolonged skin contact.

Respiratory Protection: None needed for normal use with adequate ventilation.

For Bulk Processing or Workplace Use the Following Controls are Recommended

Appropriate Engineering Controls: Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.

Personal Protection:

Eye Protection: Safety goggles recommended where eye contact is possible.

Skin Protection: Wear chemical resistant gloves.

Respiratory Protection: None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear a NIOSH approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.

Work/Hygiene Practices: Wash with soap and water after handling.

9 – Physical and Chemical Properties

Appearance:	Light amber liquid	Flammable Limits: (Solvent Portion)	LEL: 0.6% UEL: 7.0%
Odor:	Mild odor	Vapor Pressure:	45 mmHg @20°C (heptane)
Odor Threshold:	Not established	Vapor Density:	3-5 (air=1)
pH:	Not Applicable	Relative Density:	0.76-0.84
Melting/Freezing Point	Not established	Solubilities:	Insoluble in water
Boiling Point/Range:	Not Determined	Partition Coefficient; n- octanol/water:	Not established
Flash Point:	29°F (-2°C) TCC	Autoignition	Not established

		Temperature:	
Evaporation Rate:	Not established	Decomposition Temperature:	Not established
Flammability (solid, gas)	Not applicable	Viscosity:	2.56 cSt @40°C
VOC:	182.4-201.6 g/L (24%)	Pour Point:	-48°C

10 – Stability and Reactivity

Reactivity: Not reactive under normal conditions

Chemical Stability: Stable

Possibility of Hazardous Reactions: May react with strong oxidizers generating heat.

Conditions to Avoid: Avoid heat, sparks, flames and other sources of ignition.

Incompatible Materials: Strong oxidizers, acids and bases.

Hazardous Decomposition Products: Carbon monoxide and carbon dioxide.

11 – Toxicological Information

Symptoms of Overexposure:

Inhalation: High concentrations may cause throat, nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

Skin Contact: May cause skin irritation with short-term exposure with redness, itching and burning of the skin. Prolonged and/or repeated contact may produce defatting and possible dermatitis.

Eye Contact: Contact may cause eye irritation. May cause redness, stinging, swelling and tearing.

Ingestion: This product has low oral toxicity. If swallowed, this material may cause irritation of the mouth, throat and esophagus. Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea, dizziness, drowsiness and other central nervous system effects. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.

Chronic Effects: None expected.

Carcinogen Status: None of the components are listed as a carcinogen or suspect carcinogen by IARC, NTP, ACGIH or OSHA.

Reproductive Toxicity: None of the components is considered a reproductive hazard.

Numerical Measures of Toxicity:

The oral toxicity of this product is estimated to be greater than 5,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria. It is an aspiration hazard

12 – Ecological Information

Ecotoxicity: Heptane: 24 hr LC50 Goldfish – 4 mg/L; 24 hr EC50 Daphnia magna – >10 mg/L

Petroleum Solvent: No ecotoxicity data available. Ingredient is expected to be toxic to the aquatic environment with long-term adverse effects.

Persistence and Degradability: Components are not readily biodegradable.

Bioaccumulative Potential: Bioaccumulation is not expected based on an assessment of the ingredients.

Mobility in Soil: No data available

Other Adverse Effects: None known.

13 - Disposal Considerations

If this product becomes a waste, it would be expected to meet the criteria of a RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations.

14 – Transportation Information

DOT Surface Shipping Description: UN1268, Petroleum Distillates, n.o.s., 3, II, LTD QTY

(Note: Shipping Papers are not required for Limited Quantities unless transported by air or vessel – each package must be marked with the Limited Quantity Mark)

IMDG Shipping Description: UN1268, Petroleum Distillates, n.o.s, 3, II, LTD QTY

ICAO Shipping Description: UN1268, Petroleum Distillates, n.o.s, 3, II

*Note: Inner packages with less than 5 liters of liquid/ 5 kg of solid are exempt from Marine Pollutant per IMDG Code 2.10.2.7 and ICAO Special Provision A197.

NOTE: WD-40 Company does not test packaging to assure that they meet the pressure and other requirements for transport by air. We do not recommend that our products be transported by air.

15 – Regulatory Information

U.S. Federal Regulations:

CERCLA 103 Reportable Quantity: This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA TITLE III:

Hazard Category For Section 311/312: Acute Health, Fire Hazard

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III

Section 313 Reporting requirements: None

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65): This product does not contain chemicals regulated under California Proposition 65.

VOC Regulations: This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules.

Canadian Environmental Protection Act: All of the ingredients are listed on the Canadian Domestic Substances List or exempt from notification.

16 – Other Information:

HMIS Hazard Rating:

Health – 1 (slight hazard), Fire Hazard – 3 (serious hazard), Physical Hazard – 0 (minimal hazard)

Revision Date: March 7, 2016

Supersedes: July 31, 2014

Revision Summary: Changes in sections 14.

Prepared by: Industrial Health & Safety Consultants, Inc. Shelton, CT, USA

Reviewed By: I. Kowalski

Regulatory Affairs Department